

MOUNTAIN MT-400

AC 100V

Standard Voltage
500W Output

PD 60W

PD 60W
Fast Charging

368 Wh

High Quality Li-ion
Cells Inside



500W/100V
AC Output



368Wh
25Ah



PD 60W
Fast Charging



Pure Sine-wave
Output

MOUNTAIN MT-400

BATTERY
ENDURANCE DESCRIPTION



10Wh
Phone
32+ times



65Wh
Laptop
5+Times



3W
Lighting
108+ Hours



60Wh
Drone
5+ Times



12W
Bluetooth Speaker
26+ Hours



100W
Projector
3+ Hours



60W
Car Refrigerator
5+Hours

► Product Description



High Capacity

368Wh (25Ah)High Capacity
High Quality Li-ion Cells Inside

Rich Interface Powerful Functions

Up to 8 devices can be charged at the
same time AC output is supported

Innovative Appearance Design

► Performance Parameter

MODEL		MT-400
BASIC	Dimension	224 × 184 × 214mm
INFORMATION	Weight	5.5Kg
	Operating Temperature	Charge:0~40°C
		Discharge:-10~40°C
	Long Duration Storage	-20~+45°C, <70%RH (within one year)
PARAMETERS	Battery Type	18650 Li-ion Cell
	Capacity	368Wh,25Ah@3.6V
	Lifecycles	≥500 cycles
	Shelf-life	1 year (after fully charged)
INPUTS (CHARGE)	DC (×2)	10~20V, Max 100W total power input
	Type-C (×2)	Max 20V, 60W per port
	Solar Panel(Optional Accessory)	Max 100W (ideal weather)
OUTPUTS	AC(×2)	100V, 60Hz, pure sine wave, total power output 500W, surge 550W
	USB-A(×2)	DC 5V/2.4A, 12W per port
	USB-A QC3.0(×2)	DC 5V/3A; 9V/2A; 12V/1.5A; Max 18W per port
	Type-C (×2)	DC 5V/3A; 9V/3A; 12V/3A; 15V/3A; 20V/3A; Max 60W per port
OTHERS	Certification	PSE; FCC; ROHS; CE; UN38.3 (Depends on the requiements of each sales area)

※ Products will constantly upgrade from market feedback, above parameters are for reference.Please refer to the user manual for products in details.

